

## VISION<sup>®</sup> MICROLETTE™

### WEIGHT (DRY)

21.3 kg (47.0 lb)

### SIZE

Height: 46.8 cm (18.4 in.)

Width: 38.1 cm (15.0 in.)

Depth: 66.0 cm (26.0 in.)

### SAMPLER VOLUME ACCURACY

0.5 to 2.5 mL: ±0.025 mL

2.5 to 5.0 mL: ±0.050 mL

5.1 to 7.5 mL: ±0.075 mL

### POWER

Input: 100-240 VAC ± 10%, 50-60 Hz, 1.5 A max

Output: 24 VDC, 3.75 A, 90 W

### SAMPLING

*\*with an optimized method*

Minimum sample interval: 1 min\* (5 min is normal)

Maximum sample interval: 998 h, 59 min (998:59)

Sample time points: 50 max

Maximum sample volume: 90% of vial capacity

### COLLECTION

13 x 100 rack: 18 x 8 test tubes, 144 total

16 x 100 rack: 18 x 8 test tubes, 144 total

12 x 32 rack: 21 x 8 vials, 168 total

Waters UPLC<sup>®</sup> rack (12 x 32): 3 trays 6 x 8 vials, 144 total

Septum: Pre-cut type only



## CELL STAND & STIRRING DRIVE

### WEIGHT

11.8 kg (26.0 lb)

### SIZE

Height: 20 cm (8 in.)

Width: 25.0 cm (10.0 in.)

Depth: 61 cm (24 in.)

### POWER (2MAG MIXCONTROL)

Voltage, Frequency: 100-240 VAC, 50/60 Hz

Power Dissipation, Phase: 0.8 A (96 W), Single

*Specifications for non-Hanson products are for reference only. Review the individual operation manuals for exact specifications*



## CIRCULATING WATERBATH

(POLYSCIENCE AP07H200)

### SIZE

Height:	44 cm (17 in.)
Width:	23 cm (9 in.)
Depth:	51 cm (20 in.)

### POWER

Voltage:	120 VAC or 230 VAC ± 10% Grounded
Frequency:	50/60 Hz
Power Dissipation, Phase:	8.8 A (1012 W), Single

*Specifications for non-Hanson products are for reference only. Review the individual operation manuals for exact specifications*

## VISION<sup>®</sup> AUTOFILL™

### WEIGHT (DRY)

14.5 kg (32.0 lb)

### SIZE

Height:	40.1 cm (15.8 in.)
Width:	28.0 cm (11.0 in.)
Depth:	47.3 cm (18.6 in.)

### POWER

Input:	100-240 VAC ± 10%, 50-60 Hz, 1.5 A max
Output:	24 VDC, 3.75 A, 90 W